



12Gb/s SAS Enterprise 2.5" SSDs

Lightning Ultra™ Gen. II SAS SSDs

Maximum bandwidth with high availability and superior data integrity for demanding big data analytics.

Features

- Full data path protection, end-to-end T10-DIF support
- Temperature-based performance control
- MTBF - 2.5 Million Hours³
- 5 Year Warranty⁴

Benefits

- High, Predictable Performance
- Industry-leading Reliability
- Highest cost-to-performance value
- High availability for large dataset analysis
- Complete vertical integration

Write-Intensive Application Workloads

- High Performance Computing (HPC)
- Oil and Gas
- Life Sciences
- Aerospace
- Engineering
- Media Editing
- Data Warehousing
- Analytics
- Indexing
- Database Logging

The Lightning Ultra™ Gen. II 12Gb/s SAS SSD doubles interface speed, providing the highest performance for mission-critical hyperscale, cloud and virtualized data center application workloads. This next generation Lightning® SSD offers a feature-rich robust design, combined with SanDisk's innovative parallel processing architecture to deliver full data path protection (T10-DIF support), temperature based power control, SED instant secure erase, an MTBF of 2.5 million hours and power fail protection. This SSD is backward-compatible with 6Gb/s SAS and offers a single firmware binary platform for seamless integration and reduced qualification times.

Lightning Ultra™ Gen. II SAS SSDs offer industry-leading predictable performance with high availability for the analysis of large data sets. Available in 19nm SLC capacities from 200GB - 800GB² and with random read/write performance of up to 199K/115K IOPS* and sequential read/write speed of up to 980/740 MB/s!/*.

These SSDs are designed for write-intensive applications such as High Performance Computing (HPC), Big Data Analytics, Data Warehousing, Database Logging, Media Editing, and Indexing, with a heavy workload comprised of a 50/50 read/write mix. This SSD offers 25 full drive writes per day (DWPD) with a limited 5 year warranty⁴.

Lightning Ultra Gen. II SAS SSDs are a product of SanDisk's vertical integration - spanning from the fabrication of the NAND technology and wafer to the manufacturing of the finished SSD. This vertical integration, results in a customized solution that takes full advantage of each component to deliver maximum performance and quality assurance. Lightning Ultra Gen. II SSDs provide high, predictable performance, industry-leading reliability, and maximum value.

Lightning Ultra™ Gen. II 12Gb/s SAS 2.5" SSDs

200GB - 800GB

Performance/IOPS	
Data Throughput (Sequential Read/Write) ¹ /*	Up to 980/740 MB/s
Total IOPS* (Random Read) 4KB - (single port)	Up to 199,000 IOPS
Total IOPS* (Random Write) 4KB - (single port)	Up to 115,000 IOPS
Interface, Capacity, and Memory Technology	
Host Interface	12Gb/s SAS
Interface Ports	Dual full-duplex
Form Factor	2.5 inch
19nm SLC User Capacities ²	200GB, 400GB, 800GB
Sector Sizes Supported	512, 520, 4K bytes/sector T10-DIF 1, DIF 2 Support
Reliability	
Unrecovered Bit Error Rate (UBER)	<1 sector in 10 ¹⁹ bits read
End-to-End Data Protection	No performance impact
Patrol Read (automatic)	No performance impact
Power-on Hours	8760 hours per year
MTBF ³	2.5 million hours
Warranty ⁴	Lesser of 5 years or maximum endurance used
Endurance	
DWPD (Random Read)	25 DWPD
Physical Dimensions	
Height (max)	15.0 mm
Width (max)	70.1 mm
Length (max)	100.45 mm
Weight	0.238 Kg
Power Consumption	
Idle	3.9 watts
Typical	5.9 watts
Environment	
Operating Temperature (ambient)	0 to 60° C
Non-operating Temperature	-40 to 85° C
Start-up Time (Power-on to Ready)	<15 seconds

Lightning Ultra™ Gen. II 12Gb/s SAS 2.5" SSDs - Ordering Information

Part Number	Capacity
SDLTMDKW-200G-5Cxx	200GB
SDLTMDKW-400G-5Cxx	400GB
SDLTMCKW-800G-5Cxx	800GB

xx - Pack Out Option:

Generic/Sample:	A1
10 Pack:	02
Bulk Pack:	03

Specifications subject to change without notice. All specifications are based on an 11W performance level.

* Performance may vary by capacity.

(1) Based on direct attached SAS performance testing, performance may be lower depending upon host device, OS and application.

(2) 1 gigabyte (GB) = 1 billion bytes. Some capacity not available for data storage.

(3) MTBF - Mean Time Between Failures based on parts stress analysis.

(4) The earlier of (I) five (5) years or (II) the time at which such Product unit's total cumulative data recorded on such unit at its S.M.A.R.T. attribute (log page 2Fh, parameter 25) or log page 11h, parameter 1 (Percentage Used Endurance Indicator) reaches 100% of the Product unit's endurance value. For more warranty information, please visit kb.sandisk.com.

© 2015 SanDisk Corporation. All rights reserved. SanDisk is a trademark of SanDisk Corporation, registered in the United States and other countries. Lightning Ultra is a trademark of SanDisk Corporation. Other brand names mentioned herein are for identification purposes only and may be the trademarks of their holder(s). Lightning ULTRA Datasheet 10.16.15.

Contact information

ESS.channelsales@sandisk.com
ESS.OEMsales@sandisk.com
businesspartners@sandisk.com

SanDisk Corporation

951 SanDisk Drive
Milpitas, CA 95035-7933, USA
T: 1-800-578-6007

For more information, please visit:

www.sandisk.com/enterprise

SanDisk®

At SanDisk, we're expanding the possibilities of data storage. For more than 25 years, SanDisk's ideas have helped transform the industry, delivering next generation storage solutions for consumers and businesses around the globe.

951 SanDisk Drive | Milpitas | CA 95035 | USA